



- Shock Resistant Excellent for applications where using electric equipment is hazardous
- Corrosion Resistant Stainless steel cover and chassis for long life
- · Versatile Interchangeability of different size flexible shafts and cleaning tools
- Speed/Torque control Shaft rotation can be set at optimum speed for each application
- No tooling required for quick disconnect of flexible shaft
- Large Wheels allow easy Maneuverability
- Time Saving Simultaneous water flush to remove deposits from tubes
- Cleanliness Foot pedal for operator convenience to activate shaft rotation and water flow to reduced water consumption and cleaner working area

Tritorc Model TATC-300 Extra Heavy Duty Pneumatic Tube Cleaning Machine includes air filter, regulator, lubricator, adjustable speed/torque control, mobile dolly, tool storage box and air foot padel. The TATC-300 uses a cleaning tool mounted to the tip of a flexible shaft, which is available in different lengths and diameters to fit the sizeof the tube to be cleaned. For wet applications as the shaft rotates inside its watertight nylon casing, the unit feeds water through the casing to the cleaning tool. A foot pedal controls shaft rotation and water flow. While the operator feeds the rotating shaft assembly through the tube, the water flushes out deposits as they are loosened.

Tube I.D.		Tube Cleaner	Motor Power		Motor Speed	Weight		Dimension		
mm	inch	Model No.	HP	kW	RPM	lbs.	Kg.	High	Wide	Deep
6.4 & UP	1/4 & UP	TATC-300	4	3.00	300-3000	64	29	38" (975mm)	22" (560mm)	16" (406mm)