

Continuous Tube Pulling Systems

Contipull

Hydraulic Tube Pulling Systems

- Light Weight Design allows higher mobility
- Small foot print suitable for confined areas
- Higher Productivity
- Low Maintenance
- Near silent operation reduces operator fatigue



Power pack (Continuous tube pulling)			
	TTP-50	TTP-75	TPP-50
Oil tank capacity (Its)	90	100	60
Oil	ISO 68	ISO 68	ISO 68
Weight (kg/lbs)	230 (506)	255 (561)	230 (506)
Drive	Electric	Electric	Pneumatic
Voltage	415v +/- 10%	415v +/- 10%	N. A.
Power in kw	3.7	5.5	4.9
Air consumption (cfm)	N.A	N.A	150
Air Pressure (psig)	N. A.	N. A.	90 psi
Control Voltage (v)	24	24	24

Tube Pulling Guns (Continuous)			
	TPG - 15	TPG - 30	TPG - 45
Pulling capacity (T @350 bar)	15	30	45
Min to Max tube O.D.	3/8" - 1"	3/8" - 1.1/2"	1" - 3"
Stub pulling capacity	- 1.1/2" O.D.	- 3" O.D.	- 4" O.D.
Pull stroke (mm)	150	150	150
Weight (kg/lbs)	25	50	61

